APDatec 18

Light weight flat hose with a PVC inner layer and woven polyester yarn inlay

Applications waste water, construction machines, pump technology, cable protection, construction drying

Structure coated fabrics, white, opaque, round woven in twill weave

Temperature -20°C up to 65°C

Properties light weight, good tensile strength, ultimate elongation, can be driven over, crush-resistant, high pressure resistance, smooth inside, weather proof, hydrolysis & microbe resistant, good ozone- & UV-resistance







Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	53,20	1,10	10,00	30,00	20,00	100	18220
76	78,20	1,10	10,00	30,00	28,60	100	18221
102	104,20	1,10	7,00	21,00	42,00	100	18222

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026