# APDatec 105 ST

PVC hose reinforced with an impact-resistant rigid PVC spiral



**Applications** liquid manure spreading, agriculture, irrigation, waste water, trailing hose application

**Structure** soft PVC, green, transparent, plastic spiral / rigid PVC

**Temperature** -25°C up to 60°C

**Properties** very robust & resistant, reinforced with shock-resistant PVC spiral, crush-resistant, smooth outside, smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof







made in Germany

| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---|---|---|---|---|---|---|---|---|
| 40 | 48,40 | 4,20 | 4,00 | 0,59 | 0,63000 | 0,43 | 0,6 | 10504000600 |
| 40 | 48,40 | 4,20 | 4,00 | 0,59 | 0,63000 | 0,57 | 0,8 | 10504000800 |
| 40 | 48,40 | 4,20 | 4,00 | 0,59 | 0,63000 | 0,71 | 1,00 | 10504001000 |



Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026