APDatec 890

Round cord made of soft PVC

Structure soft PVC, translucent

Temperature -20°C up to 65°C

Properties medium weight, good flexibility, crush-resistant, good tensile strength, ultimate elongation, can be driven over



hydrolysis resistant

microbe-resistant

made in Germany

Outer Diameter (mm)	Wall Thickness (mm)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
35,00	35,00	1,17800	29,45	25	890035
40,00	40,00	1,53880	38,47	25	890040
3,00	3,00	0,00860	0,86	100	890003
4,00	4,00	0,01540	1,54	100	890004
5,00	5,00	0,02400	2,40	100	890005
6,00	6,00	0,03460	3,46	100	890006
7,00	7,00	0,04710	4,71	100	890007
8,00	8,00	0,06150	6,15	100	890008
10,00	10,00	0,09600	9,60	100	890010
30,00	30,00	0,86560	21,64	25	890030
45,00	45,00	1,94720	48,68	25	890045

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026