APDatec 916

PTFE hose, suitable for the transport of sensitive and corrosive fluids

Applications food production & -conveying, medical devices, pharmaceutical production

Structure PTFE, translucent

Temperature -73°C up to 260°C

Properties excellent temperature resistance, very good low-temperature flexibility, smooth outside smooth inside, good oil & petrol resistance good resistance to compressed air containing mineral oil, hydrolysis & microbe resistant good ozone- & UV-resistance weather proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
2	4,00	1,00	20	42,00	127,00	2,20	100	9160041000
3	5,00	1,00	20	32,00	95,00	1,38	50	9160051050
4	6,00	1,00	36	20,00	60,00	1,85	50	9160061050
4	6,00	1,00	36	20,00	60,00	3,70	100	9160061000
5	9,00	2,00	48	29,00	88,00	3,55	50	9160081550
6	8,00	1,00	48	13,00	39,00	5,10	100	9160081000
6	8,00	1,00	48	13,00	39,00	2,55	50	9160081050
8	10,00	1,00	60	10,00	30,00	3,30	50	9160101050
9	13,00	2,00	75	14,00	42,00	4,00	50	9160121550
10	12,00	1,00	75	9,00	27,00	4,00	50	9160121050
12	14,00	1,00	75	7,00	21,00	4,75	50	9160141050

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026