VACUFLEX® VSM

Very smooth inside profile hose made of modified TPO

Applications industrial vacuum cleaners, vacuum cleaner, cleaning, sawing & milling, extraction systems

Structure TPO, grey / squirrel grey (similar RAL 7000), opaque, profile helix / solid profile helix

Temperature -50°C up to 60°C

Properties excellent flexibility, very good low-temperature flexibility, smooth inside, corrugated outside, crush-resistant, can be driven over, good flexibility restoring force after compression or bending, excellent mechanical properties, especially for higher tensile forces







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Burst Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
32	41,00	2,50	64	1,50	0,39	0,25000	6,15	25	600320250
38	47,00	1,20	80	0,75	0,25	0,40190	13,45	25	600380250

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026