

## APDatec 35

Protection spiral made of hard TPE

<b>Applications</b>	cable protection
<b>Structure</b>	TPE/E, black, opaque
<b>Temperature</b>	-20°C up to 85°C
<b>Properties</b>	good temperature resistance, good abrasion resistance, good tensile strength, ultimate elongation, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
6,35	9,35	1,50	0,02910	0,35	12	3500635
9,5	12,50	1,50	0,04100	0,49	12	3500950
12,7	16,30	1,80	0,08300	1,00	12	3501270
16	19,60	1,80	0,10000	1,20	12	3501600
19	23,80	2,40	0,12900	1,55	12	3501900
25,4	30,20	2,40	0,18300	2,20	12	3502540
28	32,80	2,40	0,20800	2,50	12	3502800
35	40,00	2,50	0,27500	3,30	12	3503500
45	52,00	3,50	0,43300	5,20	12	3504500
47,5	55,50	3,50	0,83300	10,00	12	3504750
65	78,00	6,50	1,11100	13,33	12	3506500
75	10,50	1,50	0,03300	0,40	12	3500750
80	93,00	6,50	2,00000	24,00	12	3508000
90	103,00	6,50	2,16000	25,92	12	3509000
100	113,00	6,50	2,50000	2,50	1	3510000