

APDatec 36

Protective hose made of highly tear-resistant Polyester fabric

Applications cable protection, hose protection, air & cooling technology

Structure NEO, black, opaque

Temperature -40°C up to 120°C

Properties good flexibility, good abrasion resistance, good tensile strength, can be driven over, crush-resistant, good ozone- & UV-resistance, weather proof, hydrolysis & microbe resistant



Inner Diameter (mm)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
17	0,03400	1,70	50	360017
20	0,03800	1,90	50	360020
23	0,04500	2,25	50	360023
25	0,04750	2,38	50	360025
27	0,05000	2,50	50	360027
31	0,06000	3,00	50	360031
33	0,06330	3,17	50	360033
36	0,06400	3,20	50	360036
40	0,07600	3,80	50	360040
44	0,08000	4,00	50	360044
47	0,09000	4,50	50	360047
53	0,10000	5,00	50	360053
55	0,10000	5,00	50	360055
60	0,11330	5,67	50	360060
66	0,12000	6,00	50	360066
73	0,13300	6,65	50	360073
93	0,17000	8,50	50	360093
112	0,20000	10,00	50	360112
127	0,35000	17,50	50	360127