

## APDatec 105 ST

Highly flexible PVC hose reinforced with shock resistant rigid PVC spiral

- Applications** liquid manure spreading, agriculture, agricultural technology, irrigation, waste water
- Structure** PVC / soft PVC, green, transparent, plastic spiral / rigid PVC
- Temperature** -25°C up to 60°C
- Properties** very robust & resistant, reinforced with shock-resistant PVC spiral, crush-resistant, smooth outside, smooth inside, good chemical resistance, good ozone- & UV-resistance, weather proof



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|-------------------------------|-------------------|---------------|-----------------------------|------------|----------------|
| 40                  | 48,40               | 4,20                | 4,00                          | 0,59              | 0,63000       | 0,43                        | 0,6        | 10504000600    |
| 40                  | 48,40               | 4,20                | 4,00                          | 0,59              | 0,63000       | 0,57                        | 0,8        | 10504000800    |
| 40                  | 48,40               | 4,20                | 4,00                          | 0,59              | 0,63000       | 0,71                        | 1,00       | 10504001000    |