APDatec 815

Multilayer PVC / Buna hose with high tear resistant Polyester fabric

Applications fuel delivery, compressed air, pesticides, sprayers

Structure PVC/Buna, blue, opaque

Temperature -30°C up to 80°C

Properties very good flexibility, good low-temperature flexibility, very high pressure resistance, good chemical resistance, good ozone- & UV-resistance, weather proof





made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
6	12,00	3,00	25	20,00	60,00	0,10800	10,80	100	81500600
9	15,00	3,00	35	15,00	45,00	0,13800	13,80	100	81500900
9	15,00	3,00	35	15,00	45,00	0,13800	6,90	50	81500950
13	20,00	3,50	60	10,00	30,00	0,23100	11,55	50	81501350

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026