EURO TRIX®

Universal water hose for use in industry, construction and agriculture

Applications irrigation, waste water, agriculture, sewage treatment plants, construction machines

Structure EPDM, black, opaque

Temperature -20°C up to 100°C

Properties very good flexibility, very good temperature resistance, crush-resistant, smooth inside, smooth outside, good ozone- & UV-resistance, weather proof







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
13	20,00	3,50	50	15,00	45,00	0,26500	5,30	20	26901320
13	20,00	3,50	50	15,00	45,00	0,26500	10,60	40	26901340
19	27,00	4,00	70	15,00	45,00	0,43500	8,70	20	26901920
19	27,00	4,00	70	15,00	45,00	0,43500	17,40	40	26901940
25	34,00	4,50	120	15,00	45,00	0,58000	23,20	40	26902540

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026