APDatec 928 opaque blue

Lightweight, flexible, multi-layer compressed air hose made of polyester-polyurethane

Applications compressed air, shipbuilding, sprayers, automotive engineering, battery- & accumulator technology

Structure Polyester-Polyurethane, blue, opaque, cross braid

Temperature -40°C up to 90°C

hydrolysis resistant · microbe-resistant · abrasion resistant · very smooth inside · air

made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
9	13,00	2,50	50	20,00	60,00	0,10700	5,35	50	92800950
13	18,00	2,50	65	15,00	45,00	0,16500	8,25	50	92801350
16	21,00	2,50	70	12,00	36,00	0,21000	10,50	50	92801650
19	24,00	2,50	90	10,00	30,00	0,24000	12,00	50	92801950
19	24,00	2,50	90	10,00	30,00	0,24000	6,00	25	92801925
25	29,00	2,50	120	7,00	21,00	0,28000	7,00	25	92802525

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.

Date: 21.10.2026