APDatec 85

Multi-layer Silicone hose with glass fibre fabric

Applications medical devices, sanitary

Structure silicone coated glass fabric, white, transparent

Temperature -60°C up to 200°C

Properties good flexibility, very good temperature resistance, very good low-temperature flexibility, high pressure resistance, very good chemical resistance







Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
3	9,00	3,00	17,00	51,00	0,06800	1,70	25	8500330
4	10,00	3,00	20,00	60,00	0,07920	1,98	25	8500430
5	11,00	3,00	11,60	35,00	0,09000	2,25	25	8500530
6	12,00	3,00	10,00	30,00	0,10200	2,55	25	8500630
8	15,00	3,50	8,00	24,00	0,15200	3,80	25	8500835
10	17,00	3,50	8,00	24,00	0,17800	4,45	25	8501035
12,5	19,50	3,50	6,00	18,00	0,21120	5,28	25	85012535
14	21,00	3,50	6,00	18,00	0,27120	6,78	25	8501435
16	26,00	5,00	7,30	22,00	0,33000	8,25	25	8501650
19	30,00	5,50	6,60	20,00	0,50800	12,70	25	8501955
25	37,00	6,00	5,00	15,00	0,70120	17,53	25	8502560

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 19.11.2026