

PleXus Classic

Multilayer PVC garden hose with highly tear-resistant Polyester fabric

Applications	irrigation, waste water, construction machines, sewage treatment plants, municipal services
Structure	soft PVC, yellow / zinc yellow (similar RAL 1018), opaque, cross braid
Temperature	-20°C up to 65°C
Properties	good flexibility, smooth outside, smooth inside, weather proof, good ozone- & UV-resistance, hydrolysis & microbe resistant, phthalate-free



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
12,5	17,10	2,30	55	10,00	30,00	0,13500	1,35	10	8001310
12,5	17,10	2,30	55	10,00	30,00	0,13533	2,03	15	8001315
12,5	17,10	2,30	55	10,00	30,00	0,13500	2,70	20	8001320
12,5	17,10	2,30	55	10,00	30,00	0,13360	3,34	25	8001325
12,5	17,10	2,30	55	10,00	30,00	0,13500	4,05	30	8001330
12,5	17,10	2,30	55	10,00	30,00	0,13500	6,75	50	8001350
18,6	24,00	2,70	100	8,00	24,00	0,22700	2,27	10	8001910
18,6	24,00	2,70	100	8,00	24,00	0,22700	4,54	20	8001920
18,6	24,00	2,70	100	8,00	24,00	0,22720	5,68	25	8001925
18,6	24,00	2,70	100	8,00	24,00	0,22700	11,35	50	8001950
25	32,00	4,00	140	6,00	18,00	0,46000	4,60	10	8002510
25	32,00	4,00	140	6,00	18,00	0,45520	11,38	25	8002525
25	32,00	4,00	140	6,00	18,00	0,45540	22,77	50	8002550
32	39,00	4,00	200	4,00	12,00	0,56520	14,13	25	8003225
38	46,00	5,00	240	3,00	9,00	0,83000	20,75	25	8003825