

### APDatec 890

Round cord made of soft PVC

- Structure** PVC / soft PVC, translucent
- Temperature** -20°C up to 65°C
- Properties** medium weight, good flexibility, crush-resistant, good tensile strength, ultimate elongation, can be driven over



| Outer Diameter (mm) | Wall Thickness (mm) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------|-----------------------------|------------|----------------|
| 35,00               | 35,00               | 1,17800       | 29,45                       | 25         | 890035         |
| 40,00               | 40,00               | 1,53880       | 38,47                       | 25         | 890040         |
| 3,00                | 3,00                | 0,00860       | 0,86                        | 100        | 890003         |
| 4,00                | 4,00                | 0,01540       | 1,54                        | 100        | 890004         |
| 5,00                | 5,00                | 0,02400       | 2,40                        | 100        | 890005         |
| 6,00                | 6,00                | 0,03460       | 3,46                        | 100        | 890006         |
| 7,00                | 7,00                | 0,04710       | 4,71                        | 100        | 890007         |
| 8,00                | 8,00                | 0,06150       | 6,15                        | 100        | 890008         |
| 10,00               | 10,00               | 0,09600       | 9,60                        | 100        | 890010         |
| 30,00               | 30,00               | 0,86560       | 21,64                       | 25         | 890030         |
| 45,00               | 45,00               | 1,94720       | 48,68                       | 25         | 890045         |