

## APDatec 630 N

Light weight and highly flexible warm air hose made from PVC coated polyester fabric

|                     |                                                                                                                                                                               |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applications</b> | tent heating, air supply, heating, construction drying, asbestos removal                                                                                                      |
| <b>Structure</b>    | coated fabrics / Neoprene® coated polyester fabric coated fabrics / PVC coated polyester fabric, yellow, opaque                                                               |
| <b>Temperature</b>  | -24°C up to 150°C                                                                                                                                                             |
| <b>Properties</b>   | very good flexibility, excellent axial compressibility, good tensile strength, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof, self-extinguishing |



hydrolysis  
resistant



microbe-  
resistant



high  
temperature



air

| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Vacuum Max. (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------|---------------|-----------------------------|------------|----------------|
| 305                 | 310,00              | 0,25                | 153                 | 0,10              | 0,36300       | 2,76                        | 7,6        | 630305         |
| 425                 | 430,00              | 0,25                | 212                 | 0,10              | 0,68900       | 5,24                        | 7,6        | 630425         |
| 525                 | 530,00              | 0,25                | 262                 | 0,10              | 0,98000       | 7,45                        | 7,6        | 630525         |