

APDatec 85

Multi-layer Silicone hose with glass fibre fabric

Applications	compressed air, medical devices
Structure	silicone coated glass fabric, white, transparent
Temperature	-60°C up to 200°C
Properties	good flexibility, very good temperature resistance, very good low-temperature flexibility, high pressure resistance, very good chemical resistance


hydrolysis
resistant

microbe-
resistant

high
temperature


liquids

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
3	9,00	3,00	17,00	51,00	0,06800	1,70	25	8500330
4	10,00	3,00	20,00	60,00	0,07920	1,98	25	8500430
5	11,00	3,00	11,60	35,00	0,09000	2,25	25	8500530
6	12,00	3,00	10,00	30,00	0,10200	2,55	25	8500630
8	15,00	3,50	8,00	24,00	0,15200	3,80	25	8500835
10	17,00	3,50	8,00	24,00	0,17800	4,45	25	8501035
12,5	19,50	3,50	6,00	18,00	0,21120	5,28	25	85012535
14	21,00	3,50	6,00	18,00	0,27120	6,78	25	8501435
16	26,00	5,00	7,30	22,00	0,33000	8,25	25	8501650
19	30,00	5,50	6,60	20,00	0,50800	12,70	25	8501955
25	37,00	6,00	5,00	15,00	0,70120	17,53	25	8502560