SUPERFLEXIBLE AO

Medium-weight and very flexible hose for suction and delivery of liquids for the yacht and caravan industry, anti-odour

Applications waste water, water drain, shipbuilding, pump technology

Structure soft PVC, white / signal white (similar RAL 9003), opaque, plastic spiral / rigid PVC

Temperature -25°C up to 50°C

Properties medium weight, very good flexibility, good low-temperature flexibility, high vacuum resistance, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof







made in France

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
19	26,00	3,50	60	10,00	0,88	0,29400	7,00	25	290190250
25	33,00	4,00	70	10,00	0,88	0,36000	9,25	25	290250250
38	48,00	5,00	110	10,00	0,88	0,74000	18,50	25	290380250

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026