

APDatec 910 blaugedeckt

Single layer Polyamide tube of PA 11/12

| | |
|---------------------|-----------------------------------------------------------------------------------------------------|
| Applications | pneumatics, automation technology & robotics, welding technology, vehicle construction, compressors |
| Structure | PA, blue, opaque |
| Temperature | -40°C up to 90°C |
| Properties | good temperature resistance, high pressure resistance, smooth inside, smooth outside |



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|---------------|-----------------------------|------------|----------------|
| 2 | 4,00 | 1,00 | 20 | 40,00 | 0,01000 | 1,00 | 100 | 9100041000 |
| 2 | 4,00 | 1,00 | 20 | 40,00 | 0,01000 | 0,50 | 50 | 910B0041050 |
| 3 | 5,00 | 1,00 | 25 | 35,00 | 0,01350 | 1,35 | 100 | 9100051000 |
| 4 | 6,00 | 1,00 | 30 | 25,00 | 0,01600 | 1,60 | 100 | 9100061000 |
| 4 | 6,00 | 1,00 | 30 | 25,00 | 0,01600 | 0,80 | 50 | 910B0061050 |
| 6 | 8,00 | 1,00 | 40 | 20,00 | 0,02260 | 2,26 | 100 | 9100081000 |
| 6 | 8,00 | 1,00 | 40 | 20,00 | 0,02260 | 1,13 | 50 | 910B0081050 |
| 8 | 10,00 | 1,00 | 60 | 15,00 | 0,03000 | 3,00 | 100 | 9100101000 |
| 9 | 12,00 | 1,50 | 75 | 17,00 | 0,05300 | 2,65 | 50 | 910B0121550 |
| 10 | 12,00 | 1,00 | 60 | 13,00 | 0,03600 | 1,80 | 50 | 9100121050 |
| 11 | 14,00 | 1,50 | 85 | 14,00 | 0,06200 | 6,20 | 100 | 9100141500 |
| 27 | 4,00 | 0,65 | 20 | 30,00 | 0,01000 | 0,50 | 50 | 910B0040650 |