VACUFLEX® VAT-Elastic

Highly flexible PVC hose with coated spring steel wire

Applications industrial vacuum cleaners, vacuum cleaner, cleaning, dust extraction, construction drying

Structure PVC, black, opaque, steel wire / spring steel wire / coated / PVC

Temperature -10°C up to 70°C, short term up to 90°C

Properties good flexibility, crush-resistant, good tensile strength, good chemical resistance, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof, weather proof, excellent mechanical properties, especially for higher tensile forces, ultra light & extremly flexible, good mechanical strength







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
25	31,00	0,50	31	1,70	0,40	0,20000	560250150
32	38,00	0,50	38	1,50	0,35	0,28000	560320150
38	44,00	0,50	44	1,40	0,30	0,34000	560380150
41	47,00	0,50	47	1,40	0,30	0,37000	560410150
44	50,00	0,50	55	1,30	0,28	0,38000	560440150
51	57,00	0,50	57	1,30	0,28	0,46000	560510150

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026