VACUFLEX® VSM-EL

Very smooth internal profile hose made of electrically conductive modified TPO

Applications	industrial vacuum cleaners, vacuum cleaner, cleaning, construction machines, extraction systems
Structure	TPO, black / jet black (similar RAL 9005), opaque, profile helix / solid profile helix
Temperature	-50°C up to 60°C
Properties	corrugated outside, smooth inside, excellent flexibility, electrically conductive (R ≤ 10^3 Ohm), good flexibility restoring force after compression or bending
Norms	ATEX 2014/34/EU







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Article Number
32	40,50	70	0,50	0,50	0,23100	610320250
38	48,00	80	0,40	0,40	0,35500	610380250
50	61,00	120	0,25	0,25	0,46400	610500250

APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen-Dülken | Germany | T +49 2163 9 49 96 0 | F +49 2163 9 49 96 29 | info@apd-schlauchtechnik.de

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will pleased to advice you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical data measured at +23°C.

Date: 25.11.2026