

APDatec 810

Flexible, multi-layer PVC hose with high-tensile polyester yarn reinforcement

Applications	compressed air, construction machines, vehicle construction, compressors, waste water
Structure	soft PVC, black, opaque, cross braid
Temperature	-20°C up to 65°C
Properties	, high pressure resistance, , good chemical resistance, good ozone- & UV-resistance, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
6	12,40	3,20	24	20,00	60,00	0,12300	6,15	50	81000650
6	12,40	3,20	24	20,00	60,00	0,12300	12,30	100	81000600
9	15,40	3,20	36	20,00	60,00	0,19000	9,50	50	81000950
9	15,40	3,20	36	20,00	60,00	0,15000	15,00	100	81000900
10	16,40	3,20	40	20,00	60,00	0,16250	16,25	100	81001000
13	21,00	4,00	52	20,00	60,00	0,26200	26,20	100	81001300
13	21,00	4,00	52	20,00	60,00	0,26200	13,10	50	81001350
16	25,60	4,80	64	20,00	60,00	0,41200	20,60	50	81001650
19	28,60	4,80	76	20,00	60,00	0,43940	21,97	50	81001950