

VIDASPIR M 141

For industrial water, in agriculture and in pumping technology

Applications	waste water, pump technology, agriculture, irrigation, waste disposal vehicles
Structure	soft PVC, grey / silver grey (similar RAL 7001), opaque, plastic spiral / rigid PVC
Temperature	-25°C up to 50°C
Properties	good flexibility, good low-temperature flexibility, crush-resistant, very high vacuum resistance, very smooth inside



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
40	49,00	4,50	5,00	0,88	0,83500	25,05	30	1410400300
51	60,40	4,70	5,00	0,88	1,00000	30,00	30	1410510300
51	60,40	4,70	5,00	0,88	1,00000	50,00	50	1410510500
63	74,00	5,50	5,00	0,88	1,45600	43,68	30	1410630300
76	87,80	5,90	3,00	0,88	1,70000	85,00	50	1410760500
76	87,80	5,90	3,00	0,88	1,70000	51,00	30	1410760300
80	92,80	6,40	3,00	0,88	2,10000	63,00	30	1410800300
90	103,20	6,60	2,00	0,88	2,21000	66,30	30	1410900300
102	116,40	7,20	2,00	0,88	2,70000	81,00	30	1411020300
110	124,40	7,20	2,00	0,88	3,19000	95,70	30	1411100300
152	224,00	9,00	1,00	0,88	5,00000	125,00	25	1411520250
203	224,00	10,40	1,00	0,88	7,70000	77,00	10	1412030100
203	224,00	10,40	1,00	0,88	7,70000	154,00	20	1412030200