

POOLFLEXX

Flexible corrugated profile hose made of modified TPO, integrated cuffs, without spiral

Applications	pool & whirlpool, swimming pool technology, filter systems, water drain, pond technology
Structure	TPO, blue, opaque
Temperature	-30°C up to 60°C
Properties	light weight, good flexibility, hydrolysis & microbe resistant, weather proof, good ozone- & UV-resistance, rot proof, floatable, cuff distance 1,5 m



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
32	39,00	3,50	80	1,50	0,39	0,17000	3,57	21	4900320060
32	39,00	3,50	80	1,50	0,39	0,17000	2,04	12	4900320120
32	39,00	3,50	80	1,50	0,39	0,17000	3,57	21	4900320210
32	39,00	3,50	80	1,50	0,39	0,17000	5,36	31,5	4900320300
32	39,00	0,60	80	1,50	0,39	0,17000	8,50	50	4900320510
32	39,00	3,50	80	1,50	0,39	0,17000	17,09	100,5	4900321005
32	39,00	3,50	80	1,50	0,39	0,21500	4,52	21	4900380210
38	45,00	3,50	95	1,50	0,39	0,21500	6,45	30	4900380300
38	45,00	0,80	95	1,50	0,39	0,21500	10,75	50	4900380510