APDatec 631

Lightweight and highly flexible hot-air hose made from PVC-coated polyester fabric



Applications tent heating, air supply, heating, construction drying, asbestos removal

Structure PVC coated polyester fabric, white, opaque, steel wire / spring steel wire / coated / PVC

Temperature -20°C up to 80°C

Properties very good flexibility, excellent axial compressibility, good tensile strength, good ozone- & UV-resistance, hydrolysis & microbe resistant, weather proof, self-extinguishing





Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
203	208,00	0,25	101	0,10	0,60700	4,61	7,6	631203
305	308,00	0,25	153	0,10	1,15000	8,74	7,6	631305
425	430,00	0,25	212	0,10	1,68000	12,77	7,6	631425
525	530,00	0,25	262	0,10	1,85000	14,06	7,6	631525

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 25.11.2026