POOLFLEXX

Flexible corrugated profile hose made of modified TPO, integrated cuffs, without spiral

Applications pool & whirlpool, swimming pool technology, filter systems, water drain, pond technology

Structure TPO, blue, opaque

Temperature -30°C up to 60°C

Properties light weight, good flexibility, hydrolysis & microbe resistant, weather proof, good ozone- & UV-resistance, rot proof, floatable, cuff distance 1,5 m







made in Germany

Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
32	39,00	3,50	80	1,50	0,39	0,17000	3,57	21	4900320060
32	39,00	3,50	80	1,50	0,39	0,17000	2,04	12	4900320120
32	39,00	3,50	80	1,50	0,39	0,17000	3,57	21	4900320210
32	39,00	3,50	80	1,50	0,39	0,17000	5,36	31,5	4900320300
32	39,00	0,60	80	1,50	0,39	0,17000	8,50	50	4900320510
32	39,00	3,50	80	1,50	0,39	0,17000	17,09	100,5	4900321005
32	39,00	3,50	80	1,50	0,39	0,21500	4,52	21	4900380210
38	45,00	3,50	95	1,50	0,39	0,21500	6,45	30	4900380300
38	45,00	0,80	95	1,50	0,39	0,21500	10,75	50	4900380510

Ocono APD Schlauchtechnik GmbH | Technologiering 12 | 41751 Viersen | Germany | T +49 2162 361950 | apd@ocono.com

All technical data, measured at 23°C, are general orientation values and are subject to production-related tolerances. Max. operating pressures apply only for short periods. Technical changes and color deviations are subject to change. Other versions are available upon request.
Date: 24.11.2026