

FLEXACIER® Super 276

Very well suited to winemaking

Applications	wine production & -conveying, food production & -conveying
Structure	soft PVC, uncolored, transparent, steel wire / spring steel wire / coated / PVC
Temperature	-40°C up to 50°C
Properties	good flexibility, A B C D1, crush-resistant, very high vacuum resistance high pressure resistance, smooth outside very smooth inside
Norms	material according to Food EU Directive (EC) No. 1935/2004 & Regulation (EC) No. 10/2011 for A, B, C, D1 certified according to Food EU Directive (EC) No. 1935/2004 & Regulation (EC) No. 10/2011 for A, B, C, D1 FDA standard 21 CFR 177.2600 & 178.2010



Inner Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Article Number
20	4,50	60	10,00	0,88	0,35000	10,50	2760200300
25	4,50	75	10,00	0,88	0,51000	15,30	2760250300
30	4,50	75	10,00	0,88	0,68000	20,40	2760300300
35	4,50	75	10,00	0,88	0,77000	23,10	2760350300
40	6,00	75	10,00	0,88	1,13000	33,90	2760400300
51	6,50	75	10,00	0,88	1,50000	45,00	2760510300
70	7,00	75	10,00	0,88	2,36000	70,80	2760700300