

GOLDSCHLANGE®

High performance water and cleaning hose

Applications	construction machines, irrigation, high pressure cleaning, municipal services, street cleaning
Structure	EPDM CR, black, opaque
Temperature	-30°C up to 100°C, short term up to 130°C
Properties	very high pressure resistance, good abrasion resistance, crush-resistant, can be driven over, very high pressure resistance, good ozone- & UV-resistance, weather proof



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Burst Pressure (bar)	Weight (kg/m)	Total Weight per Piece (kg)	Length (m)	Article Number
10	17,20	3,60	45	30,00	90,00	0,16000	6,40	40	26801040
13	20,80	3,90	50	30,00	90,00	0,22500	9,00	40	26801340
16	23,20	3,60	70	25,00	75,00	0,26000	10,40	40	26801640
19	27,80	4,40	80	25,00	75,00	0,38500	15,40	40	26801940
25	34,00	4,50	160	20,00	60,00	0,49000	19,60	40	26802540
32	43,00	5,50	175	12,00	36,00	0,76000	30,40	40	26803240
38	51,00	6,50	250	12,00	36,00	1,05000	42,00	40	26803840
50	65,00	7,50	300	10,00	30,00	1,58000	63,20	40	26805040